

**SCORPION High Capacity CPE**  
**7000 SERIES**

**SCORPION**



**SCORPION**

**Model Numbers: S200, SA200**

---

## **The best-in-class carrier grade wireless bridge**

---

SCORPION High Capacity CPE (Customer Premises Equipment) offers the most advanced features in a PtMP network with the Scorpion SA900 as the Base Station.

# SCORPION High Capacity CPE 7000 SERIES

# SCORPION

SCORPION CPE series, S200 featuring an integrated 24dBi antenna and SA200 is a standalone antenna, offers high capacity up to 200Mbps net throughput in a Point-to-MultiPoint (PtMP) network with Scorpion SA900 as the Base Station combined with ultra-low latency and best PPS delivery.

Scorpion CPE offers the flexibility to upgrade net capacity, designed for unmatched interference rejection and unique Automatic Interference Sensibility (AIS) technology guarantees stable performance with constant latency and throughput when paired in a PtMP network with SCORPION SA900 as the basestation.

SCORPION proprietary transmission protocol set a benchmark of unrivaled performance and reliability, making it the ultimate choice for future-proof wireless systems.



## High Performance Radio

- Superior net throughput – 200 Mbps
- Dynamic asymmetric capacity
- Best latency - <3 ms (typical per CPE)
- Spectral efficiency (net) 8.75 b/s/Hz
- Long range – antenna dependent\*\*
- Configurable channel bandwidth – 5/10/20/40/80MHz
- 128-bit AES encryption & MAC level authentication
- Dynamic Frequency Selection (DFS)

## Extremely Low CAPEX & OPEX

- Most competitive price
- Flexible capacity, software upgradeable
- Rugged & Reliable IP67 design
- Compact & Simple to install and maintain
- <10 Watt power consumption
- Multiple frequency bands in one radio
- State-of-the-art NMS

## Unmatched Interference Rejection

- AIS (Automatic Interference Sensibility) technology makes SCORPION the most stable wireless solution in the market.
- Time Synchronization  
- Auto Sync with its Master Unit.
- Higher capacity, longer range and diversity.
- The only solution with Hitless ACM - Adaptive Coding & Modulation.
- ACS – Automatic Channel Selection.

## Advanced Networking

- HTTP, EMS, SNMP and Telnet management
- QoS based on 802.1p, TOS & DSCP
- VLAN tagging/stripping & QinQ
- Uplink and downlink bandwidth control
- Over the air remote management

## Radio

Radio Frequency	4.8 - 6.0 GHz Country Dependent
Net Throughput	200 Mbps
Channel Size	Automatic or configurable – 5/10/20/40/80 MHz
Waveform	Advanced OFDM dual polarization Modulations – BPSK, QPSK, 16QAM, 64QAM, 256QAM
Output Power	Configurable up to +30dBm***
Handling Interference	AIS - Automatic Interference Sensibility ACM - Adaptive Coding & Modulation ACS - Automatic Channel Selection FEC - Forward Error Correction, k = 1/2, 2/3, 3/4, 5/6
Encryption & Security	128-bit AES & MAC level authentication
DFS (ETSI)	Supported

## Antenna Configurations

Model S200	24dBi (integrated)
Model SA200	Connectors for external antenna (2 x TNC Female Socket)

## Networking and Management

Topology	CPE - PtMP or PtP
Access Technology	Time Division Duplex (TDD) - dynamic or symmetric
Data Latency	<3 ms (typical per CPE)
Network Modes	Layer 2 Bridge, VLAN, QinQ VLAN, NAT, DHCP server
VLAN	Transparent, VLAN Filter, Tagging/stripping & QinQ
QoS	8 priority queues based on 802.1p, TOS and DSCP
Traffic Shaping	Bandwidth control for uplink and downlink independently
SLA (Service Level Agreement)	MIR/CIR/BE
Management	Cloudstream NMS (path profiling tool), Telnet, SNMP, HTTP, Built in throughput test and Spectrum Analyzer
Performance Management	Real time & history - logs and counters of traffic and radio data

## Physical and Environmental

Physical Interface	2x 10/100/1000 Base-T (ODU)
Connector Type	2x RJ-45
Dimensions and Weight	195 x 185 x 52mm (without time synchronization connector), <1Kg (connectorized) & 300 x 300 x 60mm, <2 Kg (Integrated Antenna)
Power	Power over Ethernet (PoE) - 48 VDC
PoE Adapter AC-DC:	
• Input Power	100-240 VAC, 47-63 Hz
• Dimensions	120 x 60 x 35mm
PoE Adapter DC-DC:	
• Input Power	10-60 VDC
• Dimensions	160 x 60 x 30mm
Power Consumption	<10W
IP Rating	IP67
Operating Temperature	-40°C to 60°C
Operating Humidity	95% non condensing

\* The actual throughput is depending on the quality of the radio link, distance and factors such as external interference.

\*\* The actual radio link distance is depending on the LOS, RSSI and will result in lower MCS data rate at longer distance.

\*\*\* The TX power should be set according to country specific regulatory requirements and should not exceed.

Wavesight Limited proprietary information. Wavesight Ltd reserves the right to make any technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products.